



200 mm



Video

	PAL	NTSC
Resolution	720 x 576	720 x 480
Frame Rate	25 fps	29.97 fps
Default File Format	AVI	AVI
Additional Formats	MP4, WMV, FLV, QuickTime, WebM, Ogg (on request)	

Audio

Microphones	1x Internal Microphone 1x External Microphone via XLR Socket (optional Phantom Power)
Speaker	1x Built-in Speaker

Hardware

Internal Storage	970GB Storage (Internal HDD)
Screen	19" Portrait LCD Touch Screen
Connectivity	1x Gigabit RJ45 Network Connection 1x External USB Port
Lighting	Integrated LED light ring

Software

Operating System	Windows 7 Pro (32 Bit)
Software	VideoBooth 3 Software with interface builder and easily customisable screen flow, graphics, audio, video and data entry options.
Result delivery	Export to USB Drive, FTP to server or copy over local network.

Specifications

Height	902 mm	35 ³ / ₆₄ inches
Width	550 mm	21 ² / ₃₂ inches
Depth	200 mm	07 ⁰ / ₈ inches
Weight	35 kg	77 lb
Power	IEC Socket with regional mains cable included. Approximately 109W Consumption (@ at 220V)	

Optional Accessories

Transit Cases	Wooden Shipping Crate.
Accessories	Lighting Controller (0-10v or DMX), Wide Angle Lens, Contact Closure Input / Output Control, Chromakey Backdrop, Fibreglass Screen Surround.

Support & Warranty

24 Months back to base warranty.
 Lifetime technical support by phone/web/email.
 Access to online help desk.